

## Vastly Superior to Fin-Tube Convection...

### COMPACT CV 21s & CV 22



**All Radiators come with:**

- Built-in thermostatic valve (TRV heads sold separately)
  - Twin bottom connections with alternate side connections
  - Adjustable wall brackets for easy mounting
  - Two (2) blind plugs and one (1) air vent
  - Colour RAL9016 white, cold rolled heavy gauge steel
- 
- Panel radiators provide both convective and radiant heat enhancing total comfort
  - Faster heat-up rate with built-in valve for smarter control (heads sold separately)
  - Optimal use of low temperature radiators outperforms high temperature fin-tube
  - Perfect solution for low temperature systems using condensing boilers, heat pumps and solar systems
  - Decorative style with finished top grille and side covers
  - Higher BTUH output than fin-tube baseboard and other heat emitters

## Low Temperature Performance



### CV21S Single Panel 24" High (600mm)


Model	Length	BTUH Outputs					
		180°F	160°F	140°F	120°F	110°F	100°F
CV21S 600-600	24"	2,744	2,113	1,701	988	741	521
CV21S 600-800	32"	3,659	2,817	2,269	1,317	988	695
CV21S 600-1000	40"	4,573	3,521	2,835	1,646	1,235	869
CV21S 600-1200	48"	5,488	4,226	3,403	1,976	1,482	1,043

### CV 22 Double Panel 16" High (400mm)

Model	Length	BTUH Outputs					
		180°F	160°F	140°F	120°F	110°F	100°F
CV22 400-600	24"	3,363	2,590	1,884	1,211	975	706
CV22 400-800	32"	4,484	3,453	2,511	1,614	1,300	942
CV22 400-900	36"	4,995	3,885	2,843	1,798	1,449	1,049
CV22 400-1000	40"	5,506	4,317	3,140	1,982	1,597	1,156
CV22 400-1200	48"	6,727	5,180	3,767	2,422	1,951	1,413
CV22 400-1400	56"	7,848	6,043	4,395	2,825	2,276	1,648
CV22 400-1600	63"	8,969	6,906	5,023	3,229	2,422	1,888

### CV 22 Double Panel 24" High (600mm)

Model	Length	BTUH Outputs					
		180°F	160°F	140°F	120°F	110°F	100°F
CV22 600-600	24"	4,570	3,519	2,559	1,645	1,325	960
CV22 600-800	32"	6,094	4,692	3,412	2,194	1,767	1,280
CV22 600-900	36"	6,856	5,279	3,839	2,468	1,988	1,418
CV22 600-1000	40"	7,617	5,865	4,265	2,742	2,209	1,560
CV22 600-1200	48"	9,140	7,038	5,119	3,290	2,651	1,919
CV22 600-1400	56"	10,663	8,211	5,971	3,839	2,879	2,026
CV22 600-1600	63"	12,187	9,384	6,825	4,387	3,534	2,259
CV22 600-1800	71"	13,710	10,557	7,677	4,936	3,702	2,605



CV 22

