

Vastly Superior to Fin-Tube Convection...

RAMO RCV 22



All Radiators come with:

- Built-in thermostatic valve (TRV heads sold separately)
 - Twin bottom connections with alternate side connections
 - Adjustable wall brackets for easy mounting
 - Two (2) blind plugs and one (1) air vent
 - Colour RAL9016 white, cold rolled heavy gauge steel
-
- Panel radiators provide both convective and radiant heat enhancing total comfort
 - Faster heat-up rate with built-in valve for smarter control (heads sold separately)
 - Optimal use of low temperature radiators outperforms high temperature fin-tube
 - Perfect solution for low temperature systems using condensing boilers, heat pumps and solar systems
 - Decorative style with finished top grille and side covers
 - Higher BTUH output than fin-tube baseboard and other heat emitters

Low Temperature Performance




RCV 22 Double Panel 16" High (400mm)

Model	Length	BTUH Outputs					
		180°F	160°F	140°F	120°F	110°F	100°F
RCV22 400-600	24"	3,363	2,590	1,884	1,211	975	706
RCV22 400-800	32"	4,484	3,453	2,511	1,614	1,300	942
RCV22 400-1000	40"	5,506	4,317	3,140	1,982	1,597	1,156
RCV22 400-1200	48"	6,727	5,180	3,767	2,422	1,951	1,413
RCV22 400-1400	56"	7,848	6,043	4,395	2,825	2,276	1,648
RCV22 400-1600	63"	8,969	6,906	5,023	3,229	2,422	1,888

RCV 22 Double Panel 24" High (600mm)

Model	Length	BTUH Outputs					
		180°F	160°F	140°F	120°F	110°F	100°F
RCV22 600-600	24"	4,570	3,519	2,559	1,645	1,325	960
RCV22 600-800	32"	6,094	4,692	3,412	2,194	1,767	1,280
RCV22 600-1000	40"	7,617	5,865	4,265	2,742	2,209	1,560
RCV22 600-1200	48"	9,140	7,038	5,119	3,290	2,651	1,919
RCV22 600-1400	56"	10,663	8,211	5,971	3,839	2,879	2,026
RCV22 600-1600	63"	12,187	9,384	6,825	4,387	3,534	2,259
RCV22 600-1800	71"	13,710	10,557	7,677	4,936	3,702	2,605



RCV 22

