

AXIOM

Specialty Products For Hydronic Systems



2025

System Feeders

AXIOM

SF100

REDESIGNED 60USG TANK

- Larger Capacity
- Improved Design
- Includes Level Gauge

Available on

- SF100
- SF100-UHP
- SF100-HP
- SF100-D
- SF100-2PRV
- SF100-D-2PRV
- SF100-2PRV-HP
- SF100-D-P
- SF100-D-P-2PRV
- SF100-D-P-4x
- SF100-SS



60 USG

Digital Mini Feeders




DMF300
17 USG



DMF150
4.5 USG



Table of Contents

Category		Page
	System Feeders	2 - 4
	Condensate Neutralizers	5 - 8
	Condensate Pumps	9 - 11
	H ₂ O Demineralizers	12 - 13
	System Cleaners	14 - 17
	Hydro-NODE	18 - 20
	PEX-Pal	21 - 23
	Sidestream Filters / Chemical Pot Feeders	24 - 25
	Alternating Motor Control	26 - 27
	Index	28 - 29



System Feeders

PressurePal

Axiom System Feeders are designed to simplify the process of maintaining the cold static fluid pressure in closed-loop heating and cooling systems. Having a reservoir of suitable make-up fluid eliminates the need for backflow prevention and helps solve many of the associated problems when using domestic water as a make-up fluid.

Applications:

System Feeders are ideal for boiler/chiller systems, snow/ice melt circuits, outside air heating/cooling glycol coils, geothermal and solar heating systems.

Features and Benefits

- * Automatically maintains a minimum system pressure at a user defined setting
- * Feeders are compatible with both water and glycol/water solutions
- * **Provides leak detection** – dropping fluid level provides immediate notice that the system is losing fluid
- * **Prevents major floods** – in the event of a system rupture, only the contents of the tank will be pumped into the system
- * All units plug into any standard 115 VAC outlet
- * Diverter valve allows easy purging of air on initial start-up and manual mixing of fluid in the tank
- * Fluid drained for service from the system can easily be recovered and used to replenish the system following service
- * Fluid level switch shuts the pump off if the storage tank level gets too low
- * Does not require any annual recertification testing

THIS



REPLACES THIS



Residential



DMF150



MF200

Light Commercial



DMF300

Commercial

Redesigned
60 USG Tank



DMF150

- * 0-45 psi (0-310 kPa)
- * 4.5 USG
- * Feature Rich Digital Pressure Controller
 - Large digital display
 - Simple up/down button set-up
 - Dry contact alarm (low level, low/high pressure)
 - Comes with wall bracket

MF200

- * 10-25 psi (70-172 kPa)
- * 6.0 USG
- * Comes with funnel to simplify filling

DMF300

- * 0-45 psi (0-310 kPa)
- * 17 USG
- * Feature Rich Digital Pressure Controller
 - Large digital display
 - Simple up/down button set-up
 - Dry contact alarm (low level, low/high pressure)
 - Comes with wall bracket

SF100

- * 5-55 psi (Higher pressure models also available)
- * 60 USG (Larger reservoir tanks also available)
- * Can be configured with multiple pumps, multiple PRV's for independent system control
- * Accumulator tank prevents internal pump from cycling
- * Eliminates the need for backflow prevention on closed-loop systems
- * ETL Listed
- * Additional configuration with multiple PRV's, pumps, & alternating control panel are available

SF100 Specialty Build Options (SF100-x-xx):

- * HP-L (100 USG, 25-85 psi)
- * 2PRV (Unit Designed for 2 Systems)
- * 2PRV-L (100 USG, 2 Systems)
- * 2PRV-HP (25-85psi, 2 Systems)
- * D-P-4x (Dual Pump, Alternating Control Panel NEMA4X)
- * UHP (35-125 psi)
- * UHP-L (100 USG, 35- 125 psi)
- * D (Dual Pump)
- * D-2PRV (Dual Pump, 2 Systems)
- * D-P (Dual Pump, Alternating Control Panel)

Custom units available upon request



System Feeders



Which System Feeder is right for you ?

Use the calculator below to determine which System Feeder will best suit your application.

Feeder Sizer

System Details :

Total System Volume (Gal):

Cold Static Fill Pressure (psi):

SELECT



[Online Calculator]

Use our (Feeder Sizer) calculator online at
https://axiomind.com/axiom_products_cat/system-feeders/

System Feeder Selection Chart

Model	System Volume	System Cold Static Fill Pressure
DMF150 (4.5 USG)	Below 285 L (75 US Gal)	0 to 310 kPa (0-45 psi)
MF200 (6 USG)	Below 285 L (75 US Gal)	69 to 170 kPa (10-25 psi)
DMF300 (17 USG)	285-1135 L (75-300 US Gal)	0 to 310 kPa (0-45 psi)
SF100 (60 USG)	1135-3030 L (300-800 US Gal)	35-380 kPa (5-55 psi)
SF100-HP (60 USG)	1135-3030 L (300-800 US Gal)	170-585 kPa (25-85 psi)
SF100-L (100 USG)	Above 3030 L (800 US Gal)	35-380 kPa (5-55 psi)

ACCESSORIES

Alarm Panel



RIA10-1-SAA

Low-Level Audible & Visual Alarm Panel for use with building management systems

Wall Bracket



MF200-1430

Wall Bracket Assembly for mounting MF200 System Feeder to the wall

Hydro-NODE Bracket



NEW

HN-3

Expansion Tank Wall Bracket comes with pressure gauge, manual air vent, two 1/2" isolation ball valves and one ETV-1

Expansion Tank Valve



ETV-1


Multi-Position Service Valve that simplifies the process of filling, isolating and servicing hydronic expansion tanks

Another innovative product from Axiom

NC-1W



JOINS OUR FAMILY OF CONDENSATE NEUTRALIZERS



NC-S "HARD PIPE KIT"
INCLUDES:



NC "FULL KIT"
INCLUDES:



Ideal for
condensing appliances

Condensate Neutralizers



NC-1 "Full Kit"

NC-1S "Hard Pipe Kit"



NC-2 "Full Kit"

NC-2S "Hard Pipe Kit"



NC-1W

"Wall mounted"

Condensate fluid that is formed inside fuel burning appliances is acidic and has the potential to harm the environment and drainage systems.

Axiom condensate neutralizers:

- Raise the pH level of the acidic condensate to a more neutral level which:
 - Prevents acidic fluid from damaging drains, sewer systems and concrete
 - Helps maintain a safe environment for bacteria in septic systems
- Made with corrosion resistant materials for long term durability
- Tanks and capsules come with connection hardware kits
- Includes an initial charge of Axiom's unique blend of LipHter⁺ neutralizing media

NeutraPal Series are designed with versatility in mind. Units can be either floor or wall mounted and are ideal for use with gas burning condensing appliances with low condensate outlets.

Features

- Compact capsules minimize the overall footprint
- Offset outlet connection increases the fluid contact time with LipHter⁺ media for maximum performance
- Ideal for residential and light commercial appliances (up to 1,000,000 btu/h)
- Three available kit options
 - NC-1 & NC-2 "Full Kit" comes with connection hardware and tubing.
 - NC-1S & NC-2S "Hard Pipe Kit" comes with 3/4 PVC socket adapters
 - NC-1W "Wall Hung" Neutralizer



NT15




NeutraPro Series are designed to neutralize large volumes of acidic condensate at higher flow rates. They are constructed of corrosion resistant polypropylene material and include 1" NPT PVC union connections.

Features

- Integral baffles that weave the acidic fluid through Axiom's unique blend of LipHter media for maximum neutralization
- Low inlet connections accommodate near floor condensate outlets
- Ideal for commercial gas-burning appliances (up to 7,000,000 btu/h)
- Integral bypass feature prevents condensate backflow

NT25






NeutraPump Series are designed for the dual purpose of neutralizing acidic condensate and pumping the fluid to a suitable location.



NT1-P



NT25-P18



NT70-AP43




Features

- Integral baffles force the acidic fluid through Axiom's Neutralizer media for maximum performance.
- Pumps come with auxiliary dry contacts in event of a high-level fluid condition
- Pumps are ETL certified and come with standard 120v plug-in connection

NT1-P Features

- Ideal for residential or light commercial appliances (up to 500,000 btu/h)
- Low profile design that can be wall or floor mounted with multiple connection options:
 - Two connections (one top inlet & one side inlet) that direct fluid through LipHter⁺ media
 - Tank is designed with baffles to weave acidic fluid
 - One connection that bypasses neutralizing media
- Pump is capable of 20-feet of vertical lift
- Pump includes high level safety switch



NT25-P18 Features

- Ideal for commercial appliances (up to 6,000,000 btu/h)
- Pump is capable of 18-feet of vertical lift at design flow rate
- 1" NPT condensate inlet connection
- Pump includes high level safety switch

NT70-AP43 Features

- Ideal for large commercial and industrial appliances (up to 20,000,000 btu/h)
- Pump is capable of 10-feet of vertical lift at design flow rate
- 1½" NPT condensate inlet connection on tank
- Multiple (1") condensate inlets on pump

Condensate Neutralizers

Which Condensate Neutralizer is right for you?

Use the calculator below to determine which Condensate Neutralizer will best suit your application.

Neutra Sizer
Appliance Details :

BTU/hr Input of the Appliance:

Condensing Appliance Efficiency:

SELECT



[Online Calculator]

Use our (Neutra Sizer) calculator online at
https://axiomind.com/axiom_products_cat/condensate-neutralizers/

Condensate Neutralizer Selection Chart

Model	BTU/hr at operating efficiency	Condensate Flow Rate
NeutralPal Series		
NC-1 & NC-1S	400,000 @ 93%	1.6 Gal/hr
NC-2 & NC-2S	1,000,000 @ 93%	4.0 Gal/hr
NC-1W	400,000 @ 93%	1.6 Gal/hr
NeutraPro Series		
NT15	3,000,000 @ 96%	20 Gal/hr
NT25	7,000,000 @ 96%	45 Gal/hr
NeutraPump Series		
NT1-P	500,000 @ 93%	1.9 Gal/hr
NT25-P18	6,000,000 @ 96%	40 Gal/hr
NT70-AP43	20,000,000 @ 96%	132 Gal/hr



P/N: NM-1



P/N: NM-1BULK



P/N: NM-1P

LiPhTer+ Replacement Media

- For residential and light commercial condensate neutralizers.
- Proven champion at neutralizing acidic condensate.
- Pellet design optimizes, fluid contact time.

Condensate Neutralizer Model Numbers	Exact Replacement Part #	Bulk Media Part #
NC-1, NC-1S, NC-1W	NM-1 x Qty 1	NM-1Bulk (15 Refills)
NT1-P	NM-1P x Qty 1	NM-1Bulk (10 Refills)
NC-2, NC-2S	NM-1 x Qty 2	NM-1Bulk (7 Refills)

LiPhTer Replacement Media

- For commercial and industrial condensate neutralizers.
- Blended media provides an effective solution to treat high volumes of acidic condensate fluid.

Condensate Neutralizer Model Numbers	Exact Replacement Part #
NT15	NM-15 x Qty 1
NT20, NT25, NT25-P18	NM-25 x Qty 1
NT70-P, NT70-AP43	NM-15 x Qty 5



P/N: NM-15



P/N: NM-25


Condensate Pumps

AXIOM

APm-33DV

ULTRA QUIET MINI SPLIT
CONDENSATE PUMP

NEW



Axi Pump™



APm-33DV

- ④ Ultra Quiet
- ④ Dual Voltage (100-240v)
- ④ Suitable for mini-split (ductless)systems

Max 33' Lift
Built in high level-switch

JOINS OUR FAMILY OF CONDENSATE PUMPS

Suitable For All HVAC Equipment

(Boilers, Furnaces, Air Conditioners)



AP23



AP23-S

- ④ 23' Lift
- ④ Low Power Draw
- ④ Tubing Kit (AP23-T only)

- ④ 23' Lift
- ④ Low Power Draw
- ④ Comes with High Level Switch
- ④ Tubing kit (AP23-ST only)



AP43-HTS

- ④ 43' Lift
- ④ Rated For High Temperature (up to 185 °F / 85 °C)
- ④ Comes with High Level Switch

Condensate Pumps




Axi-Pump Mini-Split Condensate Pump is the best solution for ductless mini-split appliances.



Pump


- ④ Max 33' Lift
- ④ Dual Voltage (100-240v)
- ④ Ultra Quiet



Reservoir & Level Sensor

- ④ Built-in high level switch
- ④ 1oz (35ml) reservoir
- ④ Stainless steel serviceable filter

Kit Contents:




- ④ Pump
- ④ Reservoir
- ④ Inlet Hose
- ④ Pump reservoir connection hose
- ④ Breather hose
- ④ Cable ties and double sided adhesive pad
- ④ Communication cable of pump
- ④ overflow alarm cable



Inlet hose



Pump-reservoir Connection hose




Breather hose



Cable ties and double-sided adhesive pad

APm - 33DV Pump Curve





Axi-Pump Condensate Pumps automatically remove the condensate fluid produced from HVAC appliances like air conditioners and dehumidifiers, and acidic water generated from high-efficiency furnaces, boilers, and tankless water heaters.



AP23

* AP23-T (Includes 20' Tubing)



AP23-S

* AP23-ST (Includes 20' Tubing)




AP43-HTS


Features and Benefits

	AP23	AP23-S	AP43-HTS
High Level Switch		✓	✓
Integral Wall Mount	✓	✓	
Multiple Inlet Holes	✓	✓	✓
Quiet Pump Operation	38 dB	38 dB	60 dB
Thermally Protected	✓	✓	✓
Corrosion Resistant Material	✓	✓	✓
Stainless Steel Pump Shaft	✓	✓	✓
Max Fluid Temperature	140°F (60°C)	140°F (60°C)	185°F (85°C)
Continuous Duty	✓	✓	✓
Minimum Fluid pH	2.3	2.3	2.3
ETL Listed	✓	✓	✓

AP23 Series Pump Curve




AP43-HTS Pump Curve



Hydronic System Protection

NEW





Domestic water with dissolved minerals & gases.



PuroPal demineralized water.



Poor water quality in hydronic systems can lead to:

- Scale Build up
- Corrosion
- Reduced System Efficiency
- Increased Maintenance Costs
- Shortened Equipment Lifespan
- Risk of Leaks and Failure



Using PuroPal Demineralizers removes minerals and salts which helps:

- Lower TDS/Hardness
- Prevent scale build up
- Reduce corrosion
- Deliver reliable water quality
- Improve long-term system efficiency
- Avoid costly repairs



Special PuroPal colour changing resin

Demineralizers prevent valuable components in closed loop hydronic systems from corroding and scaling

H₂O Demineralizers



DISPOSABLE CARTRIDGES

PuroPal-1W



NEW



PuroPal-1000

MOBILE FILLING UNITS

Mobile solutions designed to treat large amounts of water



PuroPal Leader




Leader Cart-HP

Disposable cartridges are ideal for use on job specific residential and light commercial water treatment applications. Use the PuroPal series of disposable cartridges to provide demineralized water, rather than paying a premium and transporting treated water to site or purchasing pre-blended glycol solutions. Simply carry the cartridge inside, hook up to the site's water supply with garden hose connections, and begin delivering demineralized water through the PuroPal cartridge's ion-exchange resin.

PuroPal-1W

- Disposable cartridge with a translucent exterior
 - When media is expired the resin will change from blue to beige
- Designed for single point of use applications
 - One PuroPal-1W cartridge will treat approximately 65 USG (inlet water 200ppm)



Choose a PuroPal to avoid buying/transporting water with premixed glycol solutions.

PuroPal-1000

- Robust design, easy to handle
- Larger cartridges provide increased treated fluid volume
- Cartridge can be used with the PuroPal-Meter accessory to accurately measure treated fluid volume
- One cartridge will treat approximately 265 USG (inlet water 200ppm)

PuroPal Pro Series mobile filling units incorporate a robust design with integrated metering and intelligent controls, convenient drain valve allows for ease of transportation and storage. Ideal for larger (or multiple smaller) closed-loop systems, Mobile filling units provide the most economical method to providing demineralized water at individual job sites.

PuroPal Leader

- Small footprint, floor standing mobile filling unit
- PuroPal Console provides a real-time digital display of the incoming and outgoing water quality, flow rate and the total treated demineralized water
- Resin is self-contained in field replaceable cartridges, meaning down-time is mere seconds when exchanging the cartridge
 - One cartridge will treat approximately 793 USG (inlet water 200ppm)

Chemical Solutions

AXIOM

Protect 1

Express Canister

NEW

INHIBITOR

- Provides superior protection against scale & corrosion in closed-loop systems
- Helps reduce maintenance costs
- pH neutral



AXI-THERM



Clean 5

Express Canister

NEW

CLEANER

- Helps restore heat transfer area & fluid circulation in closed-loop systems
- Removes sludge and metal oxides
- pH neutral

QUICK & CONVENIENT CHEMICAL INTRODUCTION

- Suitable for all closed-loop system metals & gaskets
- 3/4" Garden hose swivel adapter
- Clear plastic tubing helps identify when dosage is complete
- Low concentration requirement
- Treats 33USG (125L) system volume



Hydronic System Cleaners and Inhibitors

CLEANING AND PROTECTION FOR CLOSED LOOP HYDRONIC SYSTEMS

Suitable for all kinds of closed loop hydronic heating and cooling systems: traditional hydronic heating systems, chilled water systems, and geothermal systems.

Features and Benefits

- Eco-friendly chemicals do not contain harmful or hazardous substances
- Easy to use. The heating system can be cleaned both with the boiler on or off
- Neutral pH does not corrode or damage gaskets, plastics, or metals (steel, copper, and aluminum)
- Keeps the heat exchanger, pipes, and radiators clean
- Low concentration requirements (0.5 L or 16.9 oz. treats 100 L or 25 U.S. gallons of water. Dosage: 0.5%)
- Provides energy savings by reducing fuel consumption - A clean heat exchanger is an efficient exchanger
- Restores heat transfer and water circulation to their original levels
- Reduces maintenance costs. Proper fill and inhibitors lead to longer running systems



PROTECT 1

SYSTEM CORROSION AND SCALE INHIBITOR

Provides energy savings by protecting against corrosion and lime scale. Suitable for use with all metals (steel, copper, and aluminum).

Dosage: 0.4%

Available in 500mL, 2L, 20L



PROTECT 1 Express

SYSTEM CORROSION AND SCALE INHIBITOR

- ¾" Garden hose swivel adapter
- Treats 33USG (125L) system volume

Available in 300mL



CLEAN 5

SYSTEM CLEANER FOR OLD HYDRONIC SYSTEMS

Provides energy savings by removing sludge and metal oxides from old hydronic systems.

Dosage: 0.5%

Available in 500mL, 2L, 20L



CLEAN 5 Express

SYSTEM CLEANER FOR OLD HYDRONIC SYSTEMS

- ¾" Garden hose swivel adapter
- Treats 33USG (125L) system volume

Available in 300mL



CLEAN 3

SYSTEM CLEANER FOR NEW HYDRONIC SYSTEMS

Provides energy savings by removing oil residue and metal oxides from new hydronic systems.

Dosage: 0.5%

Available in 500mL, 2L, 20L



CLEAN 10

SYSTEM AND BOILER CLEANER

Provides energy savings by removing limescale, sludge, and metal oxide incrustations inside the boiler and hydronic system.

Dosage: 5 - 10%

Available in 5L, 20L



Boiler

Boiler water and fire side cleaners remove incrustations from boiler components without damaging metal or plastic parts.

WATER SIDE CLEANER



CLEAN BOILER


BOILER WATER SIDE CLEANER

Removes metal oxides and limescale deposits from the water side of boiler's heat exchanger. Provides energy savings, reduces noise, and restores heat transfer to original levels.


Dosage: 10 to 20%

Available in 1L

Before



After



ACCESSORIES



P1-Test Kit

Axi-Therm Protect 1 Concentration Test Kit

- Colour-coded drop test for accurate Protect 1 dosage
- A single P1-Test kit can be used multiple times

SKU	Purpose	Bottle Size	Treatment Volume	Case Qty
AXTH-BOILER-1L	Boiler Water Side Cleaner	1L (33.8oz)	5 to 10 litres (1.32 to 2.64 gal)	10
AXTH-CF9AL	2-Part, Aluminum Boiler Combustion Side Cleaner	2x1L (33.8 oz)		5
AXTH-CFSTEEL-1L	Stainless Steel Boiler Combustion Side Cleaner	1L (33.8 oz)		10
AXTH-P1X-300mL	System Corrosion and Scale Inhibitor - Express	300mL (10 oz)	125 litres (33 gal)	10
AXTH-P1-500mL	System Corrosion and Scale Inhibitor	500mL (16.9oz)	100 litres (25 gal)	12
AXTH-P1-2L	System Corrosion and Scale Inhibitor	2L (67.6 oz.)	400 litres (100 gal)	6
AXTH-P1-20L	System Corrosion and Scale Inhibitor	20L (5.28 gal)	4000 litres (1060 gal)	1
AXTH-C3-500mL	Chemical Cleaner for NEW Hydronic Systems	500mL (16.9oz)	100 litres (25 gal)	12
AXTH-C3-2L	Chemical Cleaner for NEW Hydronic Systems	2L (67.6 oz.)	400 litres (100 gal)	6
AXTH-C3-20L	Chemical Cleaner for NEW Hydronic Systems	20L (5.28 gal)	4000 litres (1060 gal)	1
AXTH-C5X-300mL	Chemical Cleaner for OLD Hydronic Systems - Express	300mL (10 oz)	125 litres (33 gal)	10
AXTH-C5-500mL	Chemical Cleaner for OLD Hydronic Systems	500mL (16.9oz)	100 litres (25 gal)	12
AXTH-C5-2L	Chemical Cleaner for OLD Hydronic Systems	2L (67.6 oz.)	400 litres (100 gal)	6
AXTH-C5-20L	Chemical Cleaner for OLD Hydronic Systems	20L (5.28 gal)	4000 litres (1060 gal)	1
AXTH-C10-5L	System & Boiler Cleaner	5L (1.32 gal)	50 to 100 litres (12.5 to 25 gal)	4
AXTH-C10-20L	System & Boiler Cleaner	20L (5.28 gal)	200 to 400 litres (50 to 100 gal)	1



Fire Side Cleaners

Axi-Therm unique combustion-side chemical treatments quickly help clean and restore the heat transfer area of condensing appliances back to near new levels.

- Restores combustion operating efficiency to near new levels by cleaning fume-side encrustations developed during the process of combustion
- Comes with extension nozzle to help access hard to reach areas inside heat exchangers
- Chemical is formulated to help reduce time on-site by breaking the bond between encrusted combustion residue and the surface of the heat exchanger. Simply spray, let the treatment sit, brush and thoroughly rinse away


CLEAN F-STEEL



After



CLEAN F9-AL



After

CLEAN F-STEEL

Combustion cleaner for stainless-steel heat exchangers.



After



CLEAN F9-AL

Two-step combustion cleaner for aluminum heat exchangers.



Before

After



STEP 1

STEP 2



Hydro-NODE

Expansion Tank Brackets



HN-1



HN-2



HN-3



HN-3



Expansion Tank Service Valve



The Hydro-NODE is an easy connect wall bracket designed to mount the critical hydronic system components in a convenient location.

Hydro-NODE



Hydro-NODE

HN-1



The Hydro-NODE is an easy connect bracket designed to mount critical hydronic system components in a convenient location.

Features

- * Securely mount critical hydronic components
- * Provides means for easy servicing of expansion tank
- * Powder-coated for professional finish

HN-1

- * Robust welded-steel bracket
- * Bracket includes five individual NPT connections
 - Three 1/2" FNPT open connections
 - Two 1/4" FNPT open connections

HN-2



HN-2

Includes the same robust welded-steel bracket as the HN-1 and comes fully assembled with the following connections:

- * Three 1/2" FNPT ball valve connections
 - Expansion tank connection (suitable for up to 12" diameter tanks)
 - System feeder or fill inlet connection
 - Closed loop hydronic system connection
- * Two 1/4" FNPT connections
 - 1/4" manual air vent
 - 1/4" FNPT plugged connection for accessory component

HN-3



NEW

HN-3


Includes the same robust welded-steel bracket as the HN-1 and comes fully assembled with the following connections:

- * One 1/2" 3-way Expansion Tank Valve with Hose drain
- * Two 1/2" FNPT ball valve connections
 - System Feeder or fill-inlet connections
 - Closed loop hydronic system connection
- * One 1/4" manual air vent
- * One 1/4" pressure gauge



Hydro-NODE

Hydro-NODE



*Valves come with removable handles for anti-tampering purposes

ETV-1




Expansion Tank Service Valve


The ETV-1 expansion tank service valve simplifies the process of filling, isolating, draining, and servicing a hydronic expansion tank.

- * Forged brass ball valves with blow-out proof stem
- * 1/2" Multi-function 3-way valve enables contractors to:
 - Isolate and drain expansion tank
 - Isolate and drain the closed-loop system
 - Fill the closed-loop system
- * 1/2" MNPT x FNPT x GHT connections
- * Replaces multiple components and reduces installation time


Valve Positions




Normal Operation



Fill / Drain System & Expansion Tank



Fill / Drain Expansion Tank



Fill / Drain System

PEX Tubing Organizer

AXIOM

PEX-PalTM




PEX-Jr

Ideal for over-pour radiant floor heating



PEX-Pal



Ideal for in-floor high mass radiant floor heating



3-2 inch



PEX Tubing Organizer

PEX-PalTM



PEX-Pal






EndPlate

PEX-Pal tubing organizer collects and organizes in-floor tubing used in high-mass radiant floor heating installations.

Features


- Units are designed as modular blocks that quickly and easily snap together to match the number of loops on the manifold
- Two-channel design positions both the supply and return piping with the appropriate spacing required for connections to the manifold
- Modules are constructed of a high impact strength plastic suitable to be embedded in a concrete slab
- Enclosed design protects the tubing at the poured- floor surface
- Modules are designed to connect together with outlets orientated in opposite directions, for manifold applications located on interior walls, accommodating piping routed in opposite directions
- Can be easily secured in place to available decking, rebar, readyrod, temporary manifold support or wooden forms, prior to concrete being poured
- Designed to maintain manufacturers' recommended minimum bend radius for $3/4$ " and smaller diameter plastic piping

Product	Description	Box Qty
PEX-Pal	Two-channel tubing organizer module for (up to $3/4$ " Pex)	40
EndPlate	EndPlate for PEX-Pal	10





PEX-Pal Jr



PEX-Jr



The PEX-Pal Jr tubing organizer is a stand-up bracket that allows you to easily collect and organize in-floor tubing commonly used in over-pour radiant floor heating installations.

Features

- Modules protect the tubing at the floor surface
- Ideal for over-pour radiant installations
- Multiple modules press-fit together to match the number of loops on the manifold
- Each PEX-Pal Jr module fits two 1/2" PEX tubing runs (supply/return)
- Compact module design fits inside 2" x 4" interior wall
- Outlets can be reversed for manifold locations with piping in opposite directions
- Enclosed sides eliminate the need for an endplate
- Multiple mounting options (screwed to floor, backplate, or secured with rebar)
- Constructed of high impact polystyrene
- Designed to maintain manufacturers' recommended minimum bend radius for 1/2" plastic piping

Product	Description	Box Qty
PEX-Jr	Stand-up tubing module (for two 1/2" tubing runs)	12

Sidestream Filters

FillerPak

SFP SERIES



SFP-10
SFP-20

FH SERIES



FH-10
FH-20

Hydronic Sidestream Filter Packages deliver effective ongoing protection against the damaging effects of debris in all types of closed-loop hydronic systems. Ensuring the fluid in a closed-loop hydronic system is clean helps reduce overall maintenance and operating costs of the system. Monitoring and maintaining clean hydronic system fluid is now simple and convenient.

Max Temperature: 200°F (93°C)

Max Pressure: 125psi (860kPa)

Connections:

SFP-10, FH-10 3/4" FNPT

SFP-20, FH-20 1" FNPT

Features

- Brass and stainless-steel construction
- Manual balancing valve incorporates flow balancing with memory stop, filter cartridge isolation and an integral manual air vent
- Comes with standard DOE 25 micron cotton wound filter cartridge
 - 5 and 10 micron filter options available
- Filter Housing uses a double O-ring for reliable leak-free use
 - Includes ball valve drain valve with hose connection to ensure safe, mess free fluid handling
 - Can be used for chemical dosing up to 0.8 USG (3.0L)

Model	Connections	Sidestream Flow Rate	Filter Size	Filter Options (micron rating)	Vessel Volume
SFP-10 (FH-10)	3/4" FNPT	1-10 GPM (System <200GPM)	10" DOE cotton wound	5, 10, 25	0.4 gal (1.5L)
SFP-20 (FH-20)	1" FNPT	1-20 GPM (System <400GPM)	20" DOE cotton wound	5, 10, 25	0.8 gal (3.0L)

ASFI SERIES



ASFI-075
ASFI-100

Sight Flow Indicators

Max Temperature: 200°F (93°C)

Max Pressure: 125psi (860kPa)

Connections:

ASFI-075 3/4" FNPT

ASFI-100 1" FNPT

- Sight Flow Indicator provides a quick indication of the 'health' of the fluid and detects the presence of flow
- Rebuild kits available (glass, gaskets, and opening tool)



CHEMICAL BY-PASS FEEDERS

CBF SERIES



Chemical By-Pass Feeders provide simple delivery of chemicals to any closed loop system

Max Pressure and Temperature: 265psi (1.83MPa) at 200°F (93°C)
Connections: 300psi (2.07MPa) models available
FNPT (3/4")

Features

- Allows for safe and easy chemical dosing
- Ball valves for easy chemical dosing and pot feeder isolation
- Graduated funnel with stainless steel filter for clean, accurate, and mess free chemical addition
- Pressure vessel and fittings made with brass and carbon steel
- 2 Gallon (7.6L) models comes with wall bracket
- 5 Gallon (18.9L) model comes with adjustable steel legs

Model	Size	Pressure Vessel Volume	Max Pressure
CBF-2	3/4"	2 gal (7.6L)	265psi (1.83MPa)
CBF-5	3/4"	5 gal (18.9L)	265psi (1.83MPa)
CBF-2-SS	3/4"	2 gal (7.6L)	265psi (1.83MPa)

CBF-HP SERIES



HIGH PRESSURE MODELS

Features

- Fully accessible lid
- Maximum pressure rating is 300 psi


Model	Size	Pressure Vessel Volume	Max Pressure
CBF-2-HP	3/4"	2 gal (7.6L)	300psi (2.07MPa)
CBF-5-HP	3/4"	5 gal (18.9L)	300psi (2.07MPa)

Alternating Motor Control

AMC100

The AMC100 Motor Control is designed to operate 1 or 2 devices by providing stand-by staging operations. with its configurable inputs and alarms, it can be used in a wide range of residential or commercial applications that require the control of booster pumps, sump pumps, fans, compressors or other equipment.

NEW



The sequencer includes indicator lights and a selectable audible alarm. Its unique "lag alarm" output allows for a local (and/or) remote indication of the operation of the "lag" or "stand-by" output.

Feature and Benefits

Lead-lag staging control

2 Hand/Off/Auto switches

LED indicating Lights (Power, Run, Alarm)


Dry contacts for "Motor Run"/"Low-Level"
"High-Level"/ and "Lag Alarm"

Individual overload protection
w/reset buttons


Configurable inputs (N.O or N.C)

Audible buzzer for alarm

Motor shut down on a low (or high) level



Sump Pump Application



Available Configurations :


AMC100-SP-D-0 : Sump Pump Duplex Controller

AMC100-SP-S-0 : Sump Pump Simplex Controller

AMC100-SP-D-3 : Sump Pump Duplex Controller, w/ (3) FLOAT20

AMC100-SP-S-2 : Sump Pump Simplex Controller, w/ (2) FLOAT20

Pump Up Application



Available Configurations :


AMC100-PU-D-0 : Pump-Up Duplex Controller

AMC100-PU-S-0 : Pump-Up Simplex Controller

AMC100-PU-D-4 : Pump-Up Duplex Controller, w/ (4) FLOAT20

AMC100-PU-S-3 : Pump-Up Simplex Controller, w/ (3) FLOAT20

Booster Pump Application



Available Configurations :

AMC100-BP-D-0 : Booster Pump Duplex Controller

AMC100-BP-S-0 : Booster Pump Simplex Controller

AMC100-BP-D-2 : Booster Pump Duplex Controller, w/ (2) FLOAT20

AMC100-BP-S-2 : Booster Pump Simplex Controller, w/ (2) FLOAT20

Oil Detection Application



Helps satisfy elevator
Code ASME A17.1

OIL SMART®

- Pump control and alarm components differentiate between oil and water
- Alarm visible indicator: Red beacon alarm light, yellow light for oil, white light for water, alarm test and silence buttons
- Alarm horn sounds at 85 decibels at 10 feet
- Remote monitoring dry contacts: oil, water, high Liquid



Index

Part #	Wgt (lbs.)	Page(s)
AMC100	4	26,27
AMC100-SP-D-0	4	26,27
AMC100-SP-S-0	4	26,27
AMC100-SP-D-3	9	26,27
AMC100-SP-S-2	7	26,27
AMC100-BP-D-0	4	26,27
AMC100-BP-S-0	4	26,27
AMC100-BP-D-2	7	26,27
AMC100-BP-S-2	7	26,27
AMC100-PU-D-0	4	26,27
AMC100-PU-S-0	4	26,27
AMC100-PU-D-4	11	26,27
AMC100-PU-S-3	9	26,27
AMC100-SP-OIL	-	26,27
AP23	4.5	9,11
AP23-T	5	9,11
AP23-S	4.5	9,11
AP23-ST	5	9,11
AP43-HTS	7	9,11
APm-33DV	2	9,11
ASFI-075	2	24
ASFI-100	2	24
ASFI-K	1	24
ASFI-Tool	1	24
AXTH-BOILER-1L	5	15
AXTH-C10-20L	45	14,15
AXTH-C10-5L	12	14,15
AXTH-C3-20L	45	14,15
AXTH-C3-2L	5	14,15
AXTH-C3-500ml	2	14,15
AXTH-C5-20L	45	14,15
AXTH-C5-2L	5	14,15
AXTH-C5-500ml	2	14,15
AXTH-C5X-300ml	2	14,15
AXTH-CF9AL	10	16,17
AXTH-CFSteel-1L	5	16,17
AXTH-P1-20L	45	14,15
AXTH-P1-2L	5	14,15
AXTH-P1-500ml	2	14,15
AXTH-P1X-300ml	2	14,15
AXTH-Water Test Kit	10	16
AXTH-P1-Test	1	16
CBF-2	25	25
CBF-2-HP	28	25
CBF-2-SS	25	25
CBF-5	55	25
CBF-5-HP	58	25
DMF150	10	2,3

Part #	Wgt (lbs.)	Page(s)
DMF300	15	2,3
EndPlate	0.25	22
ETV-1	1	20
EXCHBAG-1	1	12,13
FH-10	6	24
FH-20	10	24
HN-1	3	18,19
HN-2	4	18,19
HN-3	5	18,19
LEADER-CartHP	33	13
MBR-12	30	13
MF200	14	2,3
NC-1	6	5,6
NC-1S	4	5,6
NC-1W	4	5,6
NC-2	10	5,6
NC-2S	8	5,6
NM-1	3	8
NM-15	35	8
NM-1BULK	37	8
NM-1P	4	8
NM-25	40	8
NT-15	40	6
NT1-P	10	7
NT25	46	6
NT25-P18	51	7
NT70	185	7
NT70-AP43	190	7
PEX-Pal	0.75	22
Pex-Jr	0.25	23
PUROPAK-CP	7	13,15
PUROPAK-CPX	7	13,14,15
PUROPAK-P	6	13,15
PUROPAK-PX	6	13,14,15
PUROPAL-1W	5	12,13
PUROPAL-1000	14	13
PUROPAL-LEADER	50	13
PUROPAL-METER	4	13
RIA10-1-SAA	4	3,4
RIA10-1-4X	5	3,4
SF100	47	3
SF100-2240	33	3
SF100-2PRV	50	3
SF100-2PRV-HP	53	3
SF100-2PRV-L	70	3
SF100-2PRV-HP-L	72	3
SF100-D	52	3
SF100-D-2PRV	55	3




Part #	Wgt (lbs.)	Page(s)
SF100-D-P	118	3
SF100-D-P-2PRV	134	3
SF100-D-P-L	131	3
SF100-HP	50	3
SF100-L	60	3
SF100-HP-L	63	3
SF100-UHP	48	3
SF100-UHP-L	61	3

Part #	Wgt (lbs.)	Page(s)
SFP-10	10	24
SFP-10-10M	1	24
SFP-10-25M	1	24
SFP-10-5M	1	24
SFP-20	13	24
SFP-20-10M	1	24
SFP-20-25M	1	24
SFP-20-5M	1	24

Notes

AXIOM

Visit www.axiomind.com to Find a Rep in your area.



 [Axiom Industries Ltd](#)

 [@axiom_hydraulics](#)

 [Axiom Industries Ltd](#)

 www.axiomind.com

3603 Burron Avenue Saskatoon, SK, Canada S7P 0E4
Phone: 1-877-651-1815 Email: info@axiomind.com